


# ePøwerHEMS Home Energy Management Solution



## **Angile Energy**

## Striving for the "zero carbon" energy use future for human beings

Qingdao Angile Energy Tech Co., Ltd. was officially established in 2021. The founder and the core technology R&D team are all from Tsinghua University, with extensive R&D and application experience in power systems, power electronics, lithium battery management, energy storage technology and other fields. Angile Energy focuses on the R&D and application of new smart and clean power energy technologies. With energy storage technology as the core platform to connect diversified new renewable energy sources such as solar, wind and potential energy (hydropower). By incorporating cutting-edge artificial intelligence (AI), flexible power allocation, virtual power plant and other technologies, we further improve the energy utilization and help global consumers use electric energy in a safe, efficient and low-carbon manner.



## Ecosystem advantages and development

#### **01** Professional

We have an independent technology R&D team (with members from Tsinghua University) and a grid-level engineering and construction team to empower the product, design and construction to the greatest extent. We provide you with professional quality and safety through commercial standards and grid-level technology.



## **02** Technically-proven

Our residential PV-ESS products have been widely used in Europe, Asia-Pacific regions and Africa. The products have successively been certified and listed by TUV, Intertek, SGS, ICE and other institutions as well as VDE Germany, G98/99 UK and Ireland, CEI Italy, AREA Romania and other organizations. In Europe, we have deployed more than 500 systems, generating more than 5MWh of green electricity.



## 03 Experienced


We have rich experience in island micro-grids and PV energy storage and charging low-carbon parks, and have cooperated with State Grid and China Southern Power Grid to implement a number of government-enterprise power grid projects. At present, we have delivered and undertaken the operation and maintenance of more than 100 projects in China.






Smart home energy management system, i.e. household green electricity, is a comprehensive energy solution for modern household users to realize self-generation and consumption and intelligent dispatching of green electricity by installing a complete new household micro-grid composed of solar system, household energy storage system, charging set and smart energy management system. Angile Energy smart home energy management system (hereinafter referred to as "ePowerHEMS") can not only improve energy utilization efficiency and reduce electricity bills, but also enhance the independence and security of household energy and reduce the risks caused by grid fluctuations.

## ePøwerHEMS Applications









## Low-carbon & energy efficient and increasing revenues

PV power generation + energy storage, realizing self-generation and feeding surplus electricity into the grid

100% **Unlocking solar** power potential

Surplus electricity stored in energy storage system to avoid waste



30%



ePower**HEMS** Help users reduce electricity bills by up to 30%



20%



Surplus electricity Fed to the grid to generate revenues

revenue increase



<sup>\*</sup>The data presented here were obtained under controlled laboratory conditions at Angile Energy. Please note that actual results may vary depending on the user's operating environment.



### **Home Energy Management System**

## Respond to contingencies

UPS realizes seamless switching in millisecond to eliminate the power outage crisis



## Constant fresh air supply in all seasons

Keep your home always at the most comfortable temperature



#### Fish pond ecosystem

Maintain ecological balance without oxygen deficiency



## Heated swimming pool

Comfortable exercise in winter



## Refrigerators and cold storage

Keep food fresh without deterioration



## Temperate-controlled wine cellar

Escort your collection



#### 24/7 security


Security coverage around the clock

\*The data presented here were obtained under controlled laboratory conditions at Angile Energy. Please note that actual results may vary depending on the user's operating environment.



## Smart and linking the future

Real-time power monitoring ensures uninterrupted operation of smart home appliance





#### **01** Visualized power management

Traditional power systems rely on monthly meter-based billing with no demand-side control. ePowerHEMS features dedicated smart meters enabling real-time electricity monitoring on mobile phones/PCs



#### **02** Integration with smart home ecosystems

Delivers uninterrupted power for smart home appliances, enabling household circuit control and 24/7 monitoring and giving alerts for whole-house electricity generation/consumption

<sup>\*</sup>The data presented here were obtained under controlled laboratory conditions at Angile Energy. Please note that actual results may vary depending on the user's operating environment.



#### Management System

## Aesthetic integration with the building

Upgraded frameless black components to protect facades and the roof from sun exposure


### More space

Build a semi-open balcony, ventilated and shaded from the sun and rain



## **Retarding aging**


Block the sun's rays, lowering the average temperature of your roof by 5–8°C. Protect your building from the weather and help keep the exterior facade looking new



#### \*The data presented here were obtained under controlled laboratory conditions at Angile Energy. Please note that actual results may vary depending on the user's operating environment.

## Aesthetic upgrade

Adopt modern frameless components with a sense of technology to enhance the value of the whole house





## ePøwerCUBE household energy storage system



#### Full-stack technology

The hybrid inverter and the battery system are independently developed by the Tsinghua technical team to ensure the best compatibility and efficiency



#### Modular design

The whole series adopt the modular design, ensuring the inverter and battery system easily connected



#### Flexible expansion

The system is scalable, supporting up to 6 hybrid inverters connected in parallel, and the battery system capacity is up to 180kWh



#### Global certification

Our household energy storage systems are widely deployed in European markets and are well received among users



#### **Efficient conversion**

The system energy conversion efficiency is up to 98%, no energy is wasted



#### Slim cube

Integrated design reduces space occupation by 10%



## Safety certification offers multiple guarantees

## 02 Professional protection

03 Global certification

Angile

3-layers hardware + 2-layers software protection, self-developed millisecond-level arc protection, automatic power-off and voltage reduction in case of emergency, built-in fire-retardant foam to quickly contain fire hazards.


01 5-Layers guarantee

Designed with standard commercial-grade IP65 dust & water protection and C4 corrosion protection, the system can still operate normally.

Both ePowerHEMS have passed global certification and met access standards in many countries, and have been tested in extreme use environments in the laboratory to ensure their use safety for users.









#### Three-phase residential energy storage system



150% PV panel power configuration





unbalanced output



Load monitoring





120-800V battery



Off-grid 150% overload operation



Multi-stage charging/ discharging time setting



IP65 dust and water protection C4 corrosion protection



Reverse flow protection



Remote upgrade



Inverter, 5-year warranty Battery pack, 10-year warranty

Model	AE8K-H-T	AE10K-H-T	AE12K-H-T
PV (input)			
lax. PV input power (kW)		15	
lax. DC voltage (V)		1000	
IPPT voltage range (V)		180~950	
lax. DC current (A)		16+16	
ax. inverter backfeed current to the array (A)		0	
sc PV (A)		20+20	
start voltage		120	
C (input/output/EPS)			
Rated grid voltage (V)		3L/ N/ PE, 220/ 380, 230/ 400	
ated current (A)	12.2/11.6	15.2/14.5	18.2/17.4
Rated grid frequency (Hz)	50/60	50/60	50/60
Pated input active power (kW)	12	15	18
Rated input apparent power (kVA)	12	15	18
flax. input apparent power (kVA)	12	15	18
Max. input current (A)	20.3	22.7	27.2
Overload capacity	150%	120%	100%
Max. output current (A)	13.5	16.8	20.1
ystem efficiency			
MPPT efficiency		99.90%	
uropean efficiency		97%	
lax. efficiency		97.60%	
Charge/discharge efficiencya		98.5%/97.5%	
eneral information			
perating temperature range		-25~60°C(>45°C derating)	
ppology		Non-Isolated	
ltitude		<3000m	
loise		<30dB	
Protection rating		IP65	
cooling method		Natural cooling	
roduct size (mm)		550*575*244	
Veight (kg) afety certification standards		29 IEC62109-1, IEC62109-2	
MC certification standards  MC certification standards		IEC62109-1, IEC62109-2	
ertificatet		TUV CE	

Model	AES5.1-M (with auxiliary electric heating)	AES5.1-M1
Battery parameters		
Rated voltage	102.4	
Operating voltage	89.6~113.6	
Rated capacity (Ah)	50	
Energy capacity (kWh)	5.12	
Battery material	LFP (32S1P)	
Recommended charge/discharge current	25A/25A (25°C)	
Max. charge/discharge current	32A/32A(25°C)	
Charge/discharge efficiency	> 95%	
Cycle life	> 10000* Cycles	
Depth of discharge (DoD)	90%	
Operating temperature	-18°C~53°C	
Communication interface	CAN, RS485	
General information		
Dimensions of battery pack (WxHxD)	550×340×252 mm	
Battery pack weight (kg)	52	
Dimensions of battery controller (Wx HxD)	550×200×252 mm	
Weight of battery controller (kg)	9.5	
Protection rating	IIP65	
Cooling method	Natural Cooling	
Warranty period	10 Years	
EMC certification standards	IEC 61000-6-1, IEC 61000-6	
Safety certification standards	IEC/EN62477-1, IEC62619, IEC 60730 Ann	nex H, IEC63056
Environmental standards	<del>_</del>	
Transportation standards	UN38.3	
Scalability	Up to 6 modules	



### ePøwerCUBE PCST

Three-phase residential hybrid inverter











150% PV panel power configuration



Load monitoring accuracy 10W



Three-phase unbalanced output



Off-grid 150% overload operation



Reverse flow protection




Remote upgrade

Three-phase hybrid inverter			
Model	AE8K-H-T	AE10K-H-T	AE12K-H-T
PV (input)			
Max. PV input power (kW)		15	
Max. DC voltage (V)		1000	
MPPT voltage range (V)		180~950	
Max. DC current (A)		16+16	
Max. inverter backfeed current to the array (A)		0	
Isc PV (A)		20+20	
Start voltage		120	
AC (input/output)			
Rated grid voltage (V)		3L/ N/ PE, 220/ 380, 230/ 400	
Rated current (A)	12.2/11.6	15.2/14.5	18.2/17.4
Rated grid frequency (Hz)	50/60	50/60	50/60
Rated input active power (kW)	12	15	18
Rated input apparent power (kVA)	12	15	18
Max. input apparent power (kVA)	12	15	18
Max. input current (A)	20.3	22.7	27.2
Overload capacity	150%	120%	100%
Max. output current (A)	13.5	16.8	20.1
Battery input/output			
Rated voltage (V)		3L/N/PE, 220/380, 230/400	
Rated frequency (Hz)		50/60	
Apparent power (kVA)		8	
Max. power (kVA)		8	
Max. output current (A)		13.5	
System efficiency			
MPPT efficiency		99.90%	
European efficiency		97%	
Max. efficiency		97.60%	
Charge/discharge efficiency		98.5%/97.5%	
Protection function			
DC reverse-polarity protection		Yes	
Island protection		Yes	
Residual current protection		Yes	
AC short-circuit protection		Yes	
AC overvoltage protection		Yes	
Integrated DC switch		Yes Yes	
Insulation monitoring		res	
General information			
Operating temperature range		-25~60°C(>45°C derating)	
Topology		Non-Isolated	
Altitude		<3000m	
Noise		<30dB	
Protection rating		IP65	
Cooling method		Natural cooling	
Product size (mm)		550*575*244	
Weight (kg)		29	
EMC certification standards		IEC62109-1, IEC62109-2	
Safety certification standards  Certificate		IEC61000-6-1, IEC61000-6-3	
Certificate Grid-Connection Standards Ge	rmany: \/DE_AD_N 410E/41.10	TUV CE EN 50549-1:2019 EN 50549-10:2022 South Africa: NRS 0	07-2-1: 2017 Ed 2.1 Swadon: EIEC221
(refer to the certification status below)		<ul> <li>V1:2022-11 V2:2024-01 CEI 0-21: 2022-03 V1:202</li> </ul>	

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



### ePøwerCUBE BAHV











Low-temperature heating



Automatic parallel connection, without voltage limitations



Long service life



10-year warranty

Model	AES5.1-M(with auxiliary electric heating)	AES5.1-M1	
Battery parameters			
ated voltage	102.4		
perating voltage	89.6~113.6		
ated capacity (Ah)	50		
ergy capacity (kWh)	5.12		
ttery material	LFP (32S1P)		
commended charge/discharge current	25A/25A (25°C)		
ax. charge/discharge current	32A/32A(25°C)		
arge/discharge efficiency	> 95%		
cle life	> 10000* Cycles	3	
epth of discharge (DoD)	90%		
perating temperature	-18°C~53°C		
ommunication interface	CAN, RS485		
eneral information			
otection rating	IP65		
oling method	Natural Cooling		
nensions of battery pack (WxHxD)	550×340×252 mr	m	
ttery pack weight (kg)	52		
mensions of battery controller (WxHxD)	550×200×252 mr	m	
eight of battery controller (kg)	9.5		
arranty period	10 Years		
ertification -	CE		
IC certification standards	IEC 61000-6-1, IEC 6100	00-6-3	
fety certification standards	IEC/EN62477-1, IEC62619, IEC 60730	Annex H, IEC63056	
rironmental standards			
nsportation standards			
alability	Up to 6 modules		

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



#### Single-phase residential energy storage system



150% PV panel power configuration



Easy installation



IP65 dustproof and waterproof C4 anti-corrosion



Off-grid 150% overload operation



Low-temperature heating



90% DoD



Load monitoring accuracy 10W



Automatic parallel connection, without voltage limitations



Reverse flow protection

Model	AE4K6-L1-S	AE5K-L1-S	AE6K-L1-S
PV (input)			
Max. PV input power (kW)		7	
Max. DC voltage (V)		550	
MPPT voltage range (V)		180-500	
Max. DC current (A)		14+14	
Max. inverter backfeed current to the array (A)		0	
sc PV (A)		18+18	
Start voltage		125	
AC (input/output/EPS)			
Rated grid voltage (V)		L/N/PE 220/230	
Rated current (A)	20.9/20.0	22.7/21.7	27.3/26.1
Rated grid frequency (Hz)	50/60	50/60	50/60
Rated input active power (kW)	4.6	5	6
Rated input apparent power (kVA)	4.6	5	6
Max. input apparent power (kVA)	4.6	5	6
Max. input current (A)	25	25	28
Overload capacity	130%	120%	100%
Max. output current (A)	25	25	28
ystem efficiency			
IPPT efficiency		99.90%	
uropean efficiency		97%	
ax. efficiency		97.60%	
harge/discharge efficiency		97.6%/96%	
eneral information			
perating temperature range		-25-60°C(>45°Cderating)	
ppology		Non-Isolated	
ltitude oise		<2000m <30dB	
orse rotection rating		<30dB IP65	
ooling method		Natural cooling	
roduct size (mm)		550*565*232	
/eight (kg)		28	
MC certification standards		IEC61000-6-1, IEC61000-6-3	
afety certification standards		IEC62109-1, IEC62109-2	
Certificate		TUV CE	
Grid-Connection Standards		G98/G99, CEI 0-21: 2022, VDE-AR-N 4105	
(refer to the certification status below)		22-11 V2:2024-01 CEI 0-21: 2022-03 V	

Model	AES5.1-L(with auxiliary electric heating)	AES5.1-L1
Battery parameters		
Rated voltage	51.2	
Operating voltage	48-56	
Rated capacity (Ah)	100	
Energy capacity (kWh)	5.12	
Battery material	LFP (16S1P)	
Recommended charge/discharge current	50A/50A (25°C)	
Max. charge/discharge current	100A/100A (25°C)	
Charge/discharge efficiency	> 95%	
Cycle life	> 10000* Cycles	
Depth of discharge (DoD)	90%	
Operating temperature	-20°C~55°C	
Communication interface	CAN, RS485	
General information		
Dimensions of battery pack (WxHxD)	550×485×195 mm	
Battery pack weight (kg)	48	
Protection rating	IP65	
Cooling method	Natural Cooling	
Warranty period	10 Years	
Certification	CE	
EMC certification standards	IEC 61000-6-1, EC 61000	)-6-3
Safety certification standards	IEC 62619, IEC 63056, IEC 607	730 Annex H
Environmental standards		
Transportation standards	UN38.3	
Scalability	Up to 15 modules	

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



### ePøwerCUBE PCSS

Single-phase residential hybrid inverter









150% PV panel power configuration



Reverse flow protection



Load monitoring accuracy 10W



Off-grid 150% overload operation



Remote upgrade



10-year warranty

Model	AE4K6-L1-S	AE5K-L1-S	AE6K-L1-S
V (input)	ALTIO LI O	ALON ET O	ALON LI 3
		7	
ax. PV input power (kW)		7	
ax. DC voltage (V)		550	
PPT voltage range (V)		180-500	
ax. DC current (V)		14+14	
ax. inverter backfeed current to the array (A)		0	
c PV (A)		18+18	
tart voltage		125	
C (input/output)			
ated grid voltage (V)		L/N/PE 220/230	
ated current (A)	20.9/20.0	22.7/21.7	27.3/26.1
ated grid frequency (Hz)	50/60	50/60	50/60
ated input active power (kW)	4.6	5	6
ated input apparent power (WA)	4.6	5	6
lax. input apparent power (kVA)	4.6	5	6
lax. input current (A)	25	25	28
overload capacity	130%	120%	100%
flax. output current (A)	25	25	28
Battery input/output			
lax. charge/discharge power (kW)	4.6/4.6	5/5	5/5
lin. battery voltage under full load (V)	51.2	51.2	51.2
attery voltage range	45-58	45-58	45-58
Max. charge/discharge current (A)	70/90	70/100	70/100
attery type	LFP	LFP	LFP
System efficiency			
MPPT efficiency		99.90%	
uropean efficiency		97%	
Max. efficiency		97.60%	
Charge/discharge efficiency		97.6%/96%	
Protection function			
C reverse-polarity protection		Yes	
sland protection		Yes	
esidual current protection		Yes	
C short-circuit protection		Yes	
C overvoltage protection		Yes	
ntegrated DC switch		Yes	
nsulation monitoring		Yes	
General information			
perating temperature range		-25-60°C(>45°Cderating)	
opology		Non-Isolated	
ltitude		<2000m	
oise		<30dB	
rotection rating		IP65	
ooling method		Natural cooling	
roduct size (mm)		550*565*232	
/eight (kg)		28	
MC certification standards		IEC61000-6-1, IEC61000-6-3	
afety certification standards		IEC62109-1, IEC62109-2	
Certificate		TUV CE	
Grid connection standard	G9:	8/G99 CEI 0-21: 2022 VDE-AR-N 4105	
refer to the certification status in the table below)		CEI 0-21: 2022-03 \ V1:2022-11 \ V2:2024-01	

<sup>\*</sup> he above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



### ePøwerCUBE BALV

#### Low-voltage residential battery pack





Fasy installation



Remote ungrado



Low-temperature heating



Automatic parallel connection, without voltage limitations



10-year warranty



90% DoD

Model	AES5.1-L(with auxiliary electric heating)	AES5.1-L1
Battery parameters		
Rated voltage	51.2	
Operating voltage	48-56	
Rated capacity (Ah)	100	
Energy capacity (kWh)	5.12	
Battery material	LFP (16S1P)	
Recommended charge/discharge current	50A/50A (25°C)	
Max. charge/discharge current	100A/100A (25°C)	)
Charge/discharge efficiency	> 95%	
Cycle life	> 10000* Cycles	
Depth of discharge (DOD)	90%	
Operating temperature	-20°C~55°C	
Charging temperature	2°C~53°C	
Discharge temperature	-20°C~55°C	
Communication interface	CAN, RS485	
General information		
Dimensions of battery pack (W x H x D)	550×485×195 mn	n
Battery pack weight (kg)	48	•
Protection rating	IP65	
Cooling method	Natural Cooling	
Warranty period	10 Years	
Certification	CE	
- EMC certification standards	IEC 61000-6-1, IEC 610	00-6-3
	IEC 62619, IEC 63056, IEC 60	
Environmental standards	<u> </u>	
Transportation standards	UN38.3	
Scalability	Up to 15 modules	

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



#### ePøwerCUBE oges

Residential off-grid PV-ESS All-in-one Box **5K** 










UPS<20ms



Angile

Max. capacity up to 76.5kWh (additional 14 battery packs)

Smart LIFePO4 BESS All-in-One



All-in-One Integrated PCS & Ba



	Wanagement o	
Off-grid PV-ESS All-in-one Box		
Model	AE5KOGES	
PV parameters		
Standard output voltage	230Vac	
AC input voltage	220/230Vac	
Standard output power	5000VA	
AC output power	5500W	
AC output frequency	50/60Hz	
Max. AC charging current	16A	
Maximum PV input current	50A	
Max. PV input power	5200W	
Max. PV charging current	80A	
PV voltage range	120V-500V	
MPPT voltage range	120V-450V	
Switching time	10ms	
Battery parameters		
Standard battery voltage	51.2V	
Battery voltage range	40-60V	
Max. discharge current	100A	
Max. charging current	100A	
Battery capacity	5.12KWh	
Cell material	LFP lithium iron phosphate	
Number of cycles	>10000 times (25°C, 0.3C, 80%DOD, >60%C25°C)	
Operating voltage	44.8-57.6V	
Operating temperature	-20°C~40°C (charging temperature) /-40°C~45°C (discharging temperature)	
Storage temperature	-20°C~45°C	
Storage humidity	5%~95%	
Max. number of units connected in parallel	9	
General information		
Capacity	5.12kWh	
(L*W*H) actual size	680*400*430mm	
Weight	80KG	
Storage temperature	-20°C~45°C	
Relative temperature	5%~95%	
Operating temperature	-10°C∼55°C	
Protection rating	IP21 (Indoor)	
Cooling method	Natural convection and active fan cooling	
Maximum battery efficiency	94%	

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



### ePøwerCUBE oges

Residential off-grid PV-ESS All-in-one Box **3K** 





All-in-One Integrated PCS & Battery



Small for various scenarios



3kW/2.56kWh



Semi-solid state battery



UPS<20ms



Support off-grid

Off-grid PV-ESS All-in-one Box Model	AE3KOGES
PV parameters	
Max. allowable string power (W)	1500W
MPPT voltage range (VDC)	30-120
Max. DC voltage (VDC)	145
MPPT starting voltage (VDC)	≥36
Max. DC current (V)	25±0.5
Battery parameters	
Rated battery voltage (VDC)	25.6
Rated capacity of battery (Wh)	2560
Max. charging power of battery (W)	3000
Rated AC input voltage (VAC)	230
AC input voltage range (VAC)	90-280
Rated output voltage of inverter	230
Efficiency	
Max. bypass efficiency	95%
Max. efficiency in charging mode	92%
Max. efficiency in inverter mode	92%
Max. MPPT efficiency	92%
General information	
Dimension (L*W*H) (mm)	672*140*461
Weight (kg)	38.0
Ambient temperature	-10~50°C
Cooling method	Forced air cooling

<sup>\*</sup> The above data were obtained through tests under laboratory conditions at 20°C, and the actual operating environment may vary.



#### **Smart Photovoltaic Modules**



#### **Efficient conversion**

Battery conversion efficiency 26%



#### Safe and durable

25-year power generation efficiency up to8.90%



#### Simple and beautiful

Upgraded to all-black seamless design to improve the texture of the whole house

22.3% Max. conversion efficiency


0~3% Power tolerance

<1.5% Power attenuation in the first year

0.40% Annual power attenuation in 2~25 years

## **Home Energy Management System**

#### **Excess returns**




#### Mechanical parameters


Packaging information

Battery arrangement	108(6X18)	
Junction box	Split junction box, IP68	
Output line	4mm2, ± 1200mm Wire length can be customized	
Glass	Single glass, 3,2 mm coated tempered glass	
Frame	Anodized aluminum alloy frame	
Assembly weight	20.8kg	
Component size	1722 X1134 X30mm	

36 pcs/pallet 216 pcs/20-foot GP container 936 pcs/40-foot HQ container 1008 pcs/13.5 m flatbed truck 1224 pcs/17.5 m flatbed truck

\* The 17.5 m truck is marked with a 30t load capacity. Due to the inconsistent specifications the specific loading quantity shall be subject to the actual delivery.





#### Electrical performance parameters STC: AM1.5 1000W/m2 25°C NOCT: AM1.5 800W/m3 20°C 1m/s Max. power uncertainty upon test: ±3%

		10. AM1.0 1000W/III2 20 0 NO	701. AWII.0 000 W/III0 20 0 III	1/3 IVEAX. POWER directionity up	011 (03). = 070
Test conditions	LR5-54HTB415M	LR5-54HTB-420M	LR5-54HTB-425M	LR5-54HTB-430M	LR5-54HTM35M
Test conditions	STC NOCT	STC NOCT	STC NOCT	STC NOCT	STC NOCT NOCT
Max. power (Pmax/W)	415 310	420 314	425 318	430 321	435 325
Open-circuit voltage (Voc/V)	38.S3 36.46	39.03 36.65	39.23 36.83	39.43 37.02	39.63 37.21
Short-circuit current (Isc/A)	13.78 11.13	13.85 11.19	13.93 11.25	14.00 1131	14.08 11.37
Peak power voltage (Vmp/V)	32.56 29.71	32.76 29.89	32.96 30.08	33.16 30.26	3336 30.44
Peak power current (Imp/A)	12.75 10.44	12.83 10.50	12.90 10.56	12.97 10.62	13.05 10.68
Module efficiency (%)	21.3	21.5	21.8	22.0	22.3

#### **Operating parameters**

Operating temperature	-40°C-+85°C
Power tolerance	0~3%
Max. system voltage	DC1500V(IEC/UL)
Max. rated current of fuse	25A
Nominal operating temperature	45±2°C
Safety protection	Class II
Fire rating of components	ULTypel or 2 IEC Class C

#### Load capacity

Max. static load on the front side	5400Pa
Max. static load on the back	2400Pa
Hail test	Diameter 25mm, impact speed 23m/s

#### Temperature coefficient (STC test)

Temperature coefficient at short-circuit current (ISC)	+0.050%/°C
Temperature coefficient at open-circuit voltage (Voc)	-0.230%/°C
Temperature coefficient at peak power (Pmax)	0290%/°C

## **Smart Household Charging Set**











## **AE Studio** Smart Energy Management System







#### Intelligent learning, autonomous optimization

The EMS platform is embedded with AI algorithm, and supports setting and learning of electricity consumption curves and step tariffs



#### Tap to view consumption and revenues

View the consumption curve and revenues in real time on the APP, which has a user-friendly interface



#### Real-time alarm and quick troubleshooting

The system supports intelligent alarms to inform the user and the O&M team to reduce the time difference of information transmission and quickly locate problems

#### Showcase

**Type:** HEMS For Villa

Scale: 30kW PV + 10kWh EES

Location: China










**Type:** HEMS For Homestay

Scale: 22kW PV + 40kWh EES

Location: Thailand












## **Smart Home Energy Management Solution**




















## **Global Footprint**





















www.angile-energy.com
info@ae-epower.com
+86 532 8097 7189

#### Qingdao Angile Energy Tech Co., Ltd.

**Add:** Room 1401 Building 1, No.106-2 Qiuyang Rd, Chengyang District, Qingdao, Shandong, China

**Post code:** 266000

#### Foshan Angile Energy Tech Co., Ltd.

**Add:** Room 403, No.10 Hanxing E Rd, Panyu District, Guangzhou, China

**Post code:** 510495

#### Angile Energy (Guangdong) Construction Co., Ltd

Add: Room 403, No.10 Hanxing E Rd, Panyu District,

Guangzhou, China **Post code:** 510495

#### **Angile Energy European Warehouse**

Add: Industriestr. 8, Nortorf, Germany

Post code: DE-24589